



TECHNICAL DATA SHEET

Product	Anti-Microbial Spunbond Non-Woven Fabric		
Raw Material Grade	Polypropylene Homo-polymer Fiber Grade		
Decomposition Temperature	≥ 300 °C (572 ° F)		
Melting Point	140-170 °C (284-338 °F)		
Product Composition	Polypropylene Raw Material : 95%		
	Coloring Additives : 2%		
	Antimicrobial Additives : 3 %		
Anti-Microbial Activity	> 98 % reduction of microbes		
(AATCC 100-2012)* ^{&} **			
Anti-Microbial Activity	> 98 % reduction of microbes		
(ASTM E 2149 - 13a)**			
Bacterial Filtration Efficiency (BFE)	> 98 %		
(ASTM : F2101 – 2019)*			

*Sample tests conducted at BTS, MUMBAI. RO **Sample tests conducted at SITRA, COIMBATORE.

TENSILE STRENGTH PROPERTIES

S. No.	GSM	N/5cms		
		MD Force (N)	CD Force (N)	% Elongation
	Applicable Standard - WSP 130.1	Applicable Standard - WSP 110.4	Applicable Standard - WSP 110.4	Applicable Standard - WSP 110.4
1	25	≥ 25	≥ 13	≥ 40
2	30	≥ 30	≥ 15	≥ 40
3	40	≥ 56	≥ 36	≥ 50
4	50	≥ 70	≥ 45	≥ 50
5	60	≥ 84	≥54	≥ 50

OTHER INFORMATION:-

Based on silver ion technology, vital role of this fabric is to resist bacteria, fungi and algae. It contains active content of anti-microbial additive which is interferes with the microbe's cell metabolism, such that it cannot reproduce itself and hence keeping the product made of it fresh, hygienic and germfree.

VPO. RAMPUR JATTAN, KALA-AMB, DISTT: SIRMOUR, HIMACHAL PRADESH, 173030 +91 9812500040, +919812021535, +919728121535 | info@rajshreefabrics.com | www.rajshreefabrics.com